

MT932 *easy*



TECHNICAL DATA SHEET

- **Compact dimensions**
l 4.70 m x w 2.34 m x h 2.30 m
- **Max. lifting height : 9.00 m**
Max. capacity : 3.2 T
- **Optimized engine**
Engine Stage 3B without particulate filter



Easy to use



Easy to maintain



Easy to transport



MT 932	
Lifting	
Max. capacity.	3200 kg
Max. lifting height.	9 m
Max. outreach	6.35 m
Break-out force with bucket (ISO 8313)	5770 daN
Time unladen	
Lifting	8.0 s
Lowering	5.5 s
Extension	13.3 s
Retraction	8.3 s
Crowd	3 s
Dump	2.9 s
Tyres	400/80-24
Braking	
Service brake	oil immersed multi-disc braking on front/rear axles
Parking brake	oil immersed multi-disc mechanics on the front axle
Engine	
DEUTZ - STAGE 3B-Final Tier IV	
Type	TD 3.6 L
cubic capacity	3621 cm ³
Power	75 cv/55.4 kW
Max. torque	330 Nm
Injection	electronic
Cooling	water
Laden drawbar pull	7320 daN
Transmission	
torque converter	
Reversing shift	electrohydraulic control
Number of gears (forward/reverse)	4/4
Max. travel speed (may vary according to applicable regulations)	25 kph
Steering mode	4 wheel steer - 3 steering modes
Controls	
JSM® Joystick multi-function load limiter cut off system - EN15000 Norm	
Hydraulics	
Pump	gear type with priority valve 104 l/min - 260 bar
Capacities	
Hydraulic oil	128 l
Fuel	120 l
Unladen weight (with forks)	7145 kg
Dimensions	
C. Front wheel centre to carriage	1.13 m
B. Wheelbase	2.81 m
I. Rear wheel centre to rear face	0.76 m
D. Overall length to carriage	4.70 m
G1. Ground clearance	0.45 m
J. Overall width of cab	0.80 m
F. Inside tyre width	1.93 m
W. Overall width	2.34 m
U1. Overall height	2.30 m
Standard forks (length x width x thickness)	1200 x 125 x 45 mm
Turning radius (over tyres)	3.80m
Carriage rotation (crowd/dump)	13° / 134°
Noise and vibration	
Noise at driving position (LpA)	78 dB
Environmental noise (LwA)	104 dB
Vibration to whole hand/arm	<2.50 m/s ²

mm	D2 4193	J 890	R 3598	V2 3800
A 1200	E 5896	K 1260	S 7533	W 2340
B 2810	F 1930	L 45	T 3460	Y 13°
C 1128	G 450	N 1715	U1 2299	Z 134°
C1 1064	G1 435	O 125	U2 2488	
D 4696	G2 435	P2 38°	V 4770	
D1 4632	I 758	P3 53°	V1 1310	

Rough Terrain Load Chart

standard EN1459 B

Machine on tyres with forks

